

4 Channel Compact 1U 4PoE 4K&H.265 Lite Network Video Recorder

















- H.265/H.264 codec decoding
- Max 80Mbps Incoming Bandwidth
- Up to 8MP Resolution for Preview and Playback
- Up to 2ch@4K/8ch@1080P decoding
- HDMI/VGA simultaneous video output
- Support IPC UPnP, 4PoE ports

NVR421HP4-4-4K



4 Channel Compact 1U 4PoE 4K&H.265 Lite Network Video Recorder

System Overview

NVR421HP4-4-4K is the first Lite series NVR that supports for 4K and H.265 encoding technology with excellent performance at an affordable price. For applications where image details are highly required, it delivers the capability of 4K resolution processing. The NVR can be served as edge storage, central storage or backup storage with an intuitive shortcut operation menu for remote management and control.

Due to its cost-effective and easy-to-install design, this NVR is ideal for a wide range of applications such as public safety, water conservancy, transportation, city centers, education, and financial institutions.

The NVR is compatible with numerous third-party devices making it the perfect solution for surveillance systems that work independently of video management system (VMS). It features an open architecture that supports for multi-user access and is compatible with ONVIF 2.4 protocol, enabling interoperability with IP cameras.

Functions

4K Resolution

4K resolution is a revolutionary breakthrough in image processing technology. 4K delivers four times the resolution of standard HDTV 1080p cameras and offers superior picture quality and image details. 4K resolution improves the clarity of a magnified scene to view or record crisp forensic video from large areas.

High Efficiency Video Coding (H.265)

The H.265 (ITU-T VCEG) video compression standard offers double the data compression ratio at the same level of video quality, or substantially improved video quality at the same bit rate, as compared to older video compression technologies. H.265 offers such impressive compression by expanding the pattern comparison and difference-coding, improving motion vector prediction and motion region merging, and incorporating an additional filtering step called sample-adaptive offset filtering.

Intelligent Video System

Working with IVS-enabled IP cameras, the NVR recognizes and records video that contains IVS data on all IP channels. The NVR records standard intelligence at-the-edge features, as well as premium IVS features that detect abandoned or missing objects, Tripwire violations, and intrusion violations. The NVR is also capable of recording business analysis data — Facial Detection, People Counting, and Heat Map — from IP cameras with built-in Intelligent Business Analytics.

ANR (Automatic Network Replenishment Technology)

Network Video Recorders with the ANR function automatically store video data on an IP camera SD card when the network is disconnected. After recovery of the network, the NVR automatically retrieves the video data stored on the camera.

Easy4ip

The Easy4ip app is available on the iOS App Store and Google Play. It makes surveillance easy and simple, allowing you to remotely access NVR devices, view live video, receive event push notifications, and search for recorded videos from an iPhone, iPad, or Android phone at anytime from virtually anywhere!

Technical Specification		Third-party Support	
System Main Processor	Quad-core embedded processor	Third-party Support	Arecont Vision, Airlive, AXIS, Canon, Dynacolor, JVC, LG, Panasonic, Pelco, PSIA, Samsung, Sanyo, Sony, Watchnet and more
Operating System	Embedded LINUX	Network	
Aduio and Video		Interface	1 RJ-45 Port (10/100Mbps)
IP Camera Input	4 Channel	Ethernet Port	1 Independent 100Mbps Ethernet Port
Two-way Talk	1 Channel Input, 1 Channel Output, RCA	PoE	4 Ports(IEEE802.3at/af)
Display			HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP,
Interface	1 HDMI, 1 VGA	Network Function	SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, SNMP, IP Search (Support Dahua IP camera, DVR, NVS, etc.), Easy4ip
Resolution	HDMI: 3840×2160, 1920×1080, 1280×1024, 1280×720	Max. User Access	128 users
	VGA: 1920×1080, 1280×1024, 1280×720	Smart Phone	iPhone, iPad, Android
Decoding Capacity	2ch@4K(30fps)/8ch@1080P(30fps)	Interoperability	ONVIF 2.4, SDK, CGI
Multi-screen Display	4CH: 1/4	Storage	
,		Internal HDD	1 SATA III Port, Up to 6 TB capacity for each HDD
OSD	Camera title, Time, Camera lock, Motion detection, Recording	HDD Mode	Single
Recording		Auxiliary Interface	
Compression	H.265/ H.264	USB	2 ports (1 Rear USB2.0, 1 Front USB2.0)
Resolution	8Mp/ 6Mp/ 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P etc.	RS232	N/A
Record Rate	80Mbps	RS485	N/A
Bit Rate	16Kbps ~ 20Mbps Per Channel	Electrical	
Record Mode	Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Tampering,	Power Supply	DC48V/1.5A
Record Interval	Video Loss), Stop 1 ~ 120 min (default: 60 min), Pre-record: 1 ~ 30 sec, Post-record: 10 ~ 300 sec	Power Consumption	NVR: <7.5W (Without HDD)
Video Detection and Alarm		Environmental	PoE: Max 25.5W for single port, 50W in total
	Recording, PTZ, Tour, Video Push, Email, Snapshot,	Environmental Operating Conditions	-10°C ~ +55°C (+14°F ~ +131°F), 86 ~ 106kpa
Trigger Events	Buzzer and Screen Tips Motion Detection, MD Zones: 396 (22 × 18),	Storage Conditions	-20°C ~ +70°C (-4°F ~ +158°F), 0 ~ 90% RH
Video Detection	Video Loss and Tampering	Construction	20 0 1/0 0(11 1250 1/1/0 30/0 111
Alarm input	N/A	Dimensions	Compact 1U, 260mm×224.9mm×47.6mm
Relay Output	N/A	Net Weight	(10.2" x 8.9" x 1.9") 0.8kg (1.76 lb) (without HDD)
Playback and Backup		Gross Weight	1.6kg(3.53 lb)(without HDD)
Playback	4CH: 1/4	Certifications	J ,
,	Ti (0) MO 15 15	CE	EN55032, EN55024, EN50130-4, EN60950-1
Search Mode	Time /Date, MD and Exact Search (accurate to second), Smart search	FCC	Part 15 Subpart B, ANSI C63.4-2014
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera. Full Screen. Backup Selection. Digital	UL	UL60950-1

Camera, Full Screen, Backup Selection, Digital

Zoom


USB Device/Network

Backup Mode



4 Channel Compact 1U 4PoE 4K&H.265 Lite Network Video Recorder

Rear Panel



Dimensions (mm)

