

W-24VAC-9P/10A

Camera Power Supply



Model

W-24VAC-9P/10A

Features

- > Input 110V AC
- > Output 24V DC, 9 channels
- > 10 Amp Supply Current
- > Integral Surge Protection
- > Individual LED Power Indication
- > Individual PTC Output Protection
- > Max. Amp: 1.1Amp/ch



W-24VAC-9P/10A

Specifications

Model	W-24VAC-9P/10A	
Specification	240W24V10A9P	
Shape Dimension	28×20.8×8.7cm	
Weight	4.78kg	
Input	Input Voltage	110VAC
	Input Voltage Frequency	60Hz
Output	Output Voltage	24VAC±5%
	Output Current	10A, 9channels for 18sets load
Fuse	Type /Rating	PTC 1.1A/60V
Protection	Over current protection	When over current occurs, the corresponding channel output will automatically switch to self-protection status, and the other channels output work normally, when condition removed, then switch back to normal.
	short-circuit protection	When short-circuit occurs, individual PTC fuse will open the circuit, when condition removed, PTC fuse will automatically back to close.
Circumstances	Working Temperature	0℃~+40℃
	Storage temperature	-20℃~+85℃
	RH	5%~95%
	Heat release	Natural heat dissipation
Connection	Input	three-pin socket
	Output	channels output

Winic Technologies USA Inc.

42 Central Avenue, Farmingdale, New York 11735 Tel: +631-396-0800

Fax: +631-396-0805

Email:sales@winictech.com

www.winictech.com

*Design and specifications are subject to change without notice.