



## POE-SW16PG-2GF-250

16 ports High Power PoE Fiber switch 10/100Mbps UpLink




### Features

- Fully IEEE802.3af/at standard compliant
- Support PoE power up to 15.4W/30W for each PoE ports
- Auto detect powered device(PD)
- Safe and reliable power to most of PoE end device
- 10/100Mbps Supported

### Introduction

Winic 16 ports PoE Switches is 10/100M unmanaged PoE switches. It is designed for growing businesses that want control over their network.. Easy Installation and Cable Connection. As data and power are transmitted over one cable, the POE-SW16PG-2GF-250 does not need a second cable and electrical outlets on the wall, ceiling or any unreachable place. Thus, it helps to lower the installation costs and simplify the installation effort. All the RJ45 copper interfaces of the POE-SW16PG-2GF-250 support 10/100Mbps auto-negotiation for optimal speed detection through RJ45 Category 6, 5 or 5e cable. It also supports standard auto-MDI/MDI-X that can detect the type of connection to any Ethernet device without requiring special straight-through or crossover cables




# POE-SW16PG-2GF-250

## 16 ports High Power PoE Fiber switch 10/100Mbps UpLink

### Specification:

Network Standards	<ul style="list-style-type: none"> <li>• IEEE802.3i 10BASE-T</li> <li>• IEEE802.3u 100BASE-TX</li> <li>• IEEE802.3X Flow Control</li> <li>• IEEE802.3af/IEEE802.3at Power over Ethernet</li> </ul>
PoE Power	<ul style="list-style-type: none"> <li>• 15.4/25.5W per port</li> <li>• Wiring:Data provided over pairs over1/2 and3/6</li> <li>• Cable:Unshielded UPT cat.5 or higher</li> </ul>
Processing types	<ul style="list-style-type: none"> <li>• Store-and-forward</li> <li>• Half-duplex back pressure and IEEE802.3x full-duplex flow control</li> </ul>
Address database Table Size	<ul style="list-style-type: none"> <li>• 8000MAC address</li> </ul>
Backplane Bandwidth	<ul style="list-style-type: none"> <li>• 8.8Gbps</li> </ul>
Network Latency	<ul style="list-style-type: none"> <li>• Less than 20us for 64-byte frames in Store-and-forward mode for 100Mbps to 100Mbps transmission</li> </ul>
LED Indicator	<ul style="list-style-type: none"> <li>• Power, Link/Act,PoE Max</li> </ul>
Intelligent PoE Control	<ul style="list-style-type: none"> <li>• Over Temperature</li> <li>• Power Limite</li> <li>• PoE Classification</li> </ul>
Size	<ul style="list-style-type: none"> <li>• 440*285*44</li> </ul>
Weight	<ul style="list-style-type: none"> <li>• 3.88kg</li> </ul>
Working Temperature	<ul style="list-style-type: none"> <li>• Working Temperature: -10°C~40°C</li> <li>• Storing Temperature: -40°C~70°C</li> <li>• Working Humidity: 10%~90%</li> <li>• Storing Huminity: 50%~90%</li> </ul>
Network ports	<ul style="list-style-type: none"> <li>• 16 10/100 Mbps auto-sensing Fast PoE Ethernet Ports</li> <li>• 4 10/100/1000 Mbps auto-sensing Gigabit uplink Ports</li> <li>• Ethernet switching ports (RJ-45)</li> <li>• -2 Dual Personality SFP ports</li> </ul>

### Application:



### Winic Technologies USA Inc.

42 Central avenue, Farmingdale, New York 11735

Tel: +631-396-0800

Fax: +631-396-0805

Email:sales@winictech.com

www.winictech.com

Design and specifications are subject to change without notice.