

# HDC-VD105E-IR-VF

5.0 Megapixel 1944P HD 4 In 1 Cameras



- **1/2.5" 5.0 Megapixel CMOS**
- **IR Led:35pcs IR LED**
- **NTSC:5MP:20FPS/4MP:30FPS,15FPS PAL:5MP:12.5FPS/  
4MP:25FPS,12.5FPS**
- **Long Distance, No delay**
- **Support ICR auto switch**
- **Support AHD/ CVI/ TVI/ Analog transfer**



# HDC-VD105E-IR-VF

## 5.0 Megapixel 1944P HD 4 In 1 Cameras

### Specifications

Camera	
Image Sensor	1/2.5" 5.0 Megapixel CMOS
Effective Pixel	2592(H)×1944(V)
Video Frame Rate	NTSC:5MP:20FPS/ 4MP:30FPS, 15FPS PAL:5MP:12.5FPS/ 4MP:25FPS,12.5FPS
Electronic Shutter	PAL:1/50s~1/100,000s NTSC:1/50s~1/100,000s
Min.Illumination	0.01Lux@F1.2, (0Lux IR on)
OSD	Yes(Coaxial menu control)
Synchronization	Internal
TV system	PAL/NTSC
Lens	
Lens	2.8-12mm
General	
Power Supply	DC12V
Power Consumption	250mA
Working Temperature	-10° C~+50° C

### Packing Information

Unit G.W.	0.83KG
Gift Box Size	/
Package/CTN	16PCS/CTN
CTN G.W.	20KG
Meas.	661*337*340mm

### Dimensions (mm)

