

HDC-EB105M-IR-3.6B

5.0 Megapixel 1944P HD 4 In 1 Cameras



- 1/2.5" 5.0 Megapixel CMOS
- IR Led:3pcs Array
- NTSC:5MP:20FPS/4MP:30FPS,15FPS
PAL:5MP:12.5FPS/ 4MP:25FPS,12.5FPS
- Long Distance, No delay
- Support ICR auto switch
- Support AHD/ CVI/ TVI/ Analog transfer



HDC-EB105M-IR-3.6B

5.0 Megapixel 1944P HD 4 In 1 Cameras

Specifications

Camera	
Image Sensor	1/2.5" 5.0 Megapixel CMOS
Effective Pixel	2592(H)×1944(V)
Video Frame Rate	NTSC:5MP:20FPS/ 4MP:30FPS, 15FPS PAL:5MP:12.5FPS/ 4MP:25FPS,12.5FPS
Electronic Shutter	PAL:1/50s~1/100,000s NTSC:1/50s~1/100,000s
Min.Illumination	0.01Lux@F1.2, (0Lux IR on)
OSD	Yes(Coaxial menu control)
Synchronization	Internal
TV system	PAL/NTSC
Lens	
Lens	3.6mm
General	
Power Supply	DC12V
Power Consumption	250mA
Working Temperature	-10° C~+50° C

Packing Information

Unit G.W.	0.35KG
Gift Box Size	270mm*205mm*100mm
Package/CTN	36PCS/CTN
CTN G.W.	15.5KG
Meas.	465*350*278mm

Dimensions (mm)

