

## VTNS1060A

Network Power Supply for IP Systems



- Compact Unit with Aesthetic Design
- BLUE|LINE Protocol Network Power Supply Switch
- Connect up to Six (6) Indoor Monitors with CAT 5E Cable
- Transmits Signal and Power Simultaneously

# VTNS1060A



## Network Power Supply for IP Systems

Technical Specifications	
Voltage	24 V Requires a separate 24 VAC, 3 A power supply.
Power Consumption	Standby: 0.2 W, under free load Maximum: 45 W, under full load
Operating Temperature	-10° C to +55° C (14° F to +131° F)
Dimensions	178.80 mm x 107.10 mm x 30.30 mm (7.04 in. x 4.22 in. x 1.19 in.)
Net Weight	0.30 kg (0.66 lb)

### Certifications

Electromagnetic Compatibility (EMC)	FCC CFR 47 Part 15 subpart B ANSI C63.4 - 2009 EN 55022:2010/AC:2011, EN 55024:2010, EN 50130-4:2011, EN 61000-6-3:2007/A1:2011, EN 61000-3-2:2006 +A2:2009, EN 61000-3-3:2008, IEC 61000-4-2:2008, IEC 61000-4-3:2006+A1:2007+A2:2010, IEC 61000-4-4:2012, IEC 61000-4-5:2005, IEC 61000-4-6:2008, IEC 61000-4-8:2009, IEC 61000-4-11:2004
-------------------------------------	---

### Dimensions (mm/in.)

