

## POE-SW4P-2G-60

### 4-Port Fast Ethernet PoE Switch



#### Product Overview

POE-SW4P-2G-60 is a 4-port fast Ethernet switch, which supports 250 meters long distance PoE transmission. It provides 4\*10/100Mbps PoE ports and 2\*100 Mbps uplink ports. The product is equipped with two transmission modes (Default/Extend), which are controlled by DIP switch.

#### Features

- Layer two commercial switch
- Supports IEEE802.3, IEEE802.3u and IEEE802.3X standards
- MAC auto learning, aging, MAC address capacity is 2K
- Supports MDI/MDIX self-adaptation
- RJ45 port supports 10/100 Mbps self-adaptation
- Supports IEEE802.3af and IEEE802.3at power supply standards
- Adopts metal enclosure
- Supports Hi-PoE 60W
- Supports DC 48-57V power supply



# POE-SW4P-2G-60

## 4-Port Fast Ethernet PoE Switch

| Technical Specification |  |
|-------------------------|--|
| Model                   | POE-SW4P-2G-60                                       |
| Ethernet Port           | 2*10/100Mbps Uplink ports<br>4*10/100 Mbps PoE ports |
| PoE Power Consumption   | Port1≤60W, Port2-4≤30W, Total≤60W                    |
| PoE Protocol            | IEEE802.3af (PoE), IEEE802.3at (PoE+), Hi-PoE        |
| Switching Capacity      | 1.8Gbps  |
| Packet Forwarding Rate  | 890kpps  |
| Packet Buffer Memory    | 768Kb  |
| MAC Table Size          | 2K   |
| Flow Control            | Enable by default                                    |
| Application Humidity    | 10%~90%  |
| Power                   | DC48~57V power adapter                               |
| Lightning Protection    | Common Mode 2KV<br>Differential Mode 0.5KV           |
| Working Temperature     | -10°C~+55°C  |
| Weight                  | 0.3kg  |
| Dimension(W×D×H)        | 130mm×85mm×26mm                                      |