



The 1x2 HDMI Splitters uses a single HDMI source, accessing to multiple HDMI sinks. It allows one HDMI device to be split easily to 2 HDMI compatible monitors or projectors. In addition, it can be placed at the end of a long HDMI cable to regenerate the HDMI signal. The resolution of this HDMI splitter can be up to 3840x2160/30Hz.

Key Features :

- Support HDMI 1.4b
- Support Full 3D
- Support HDMI resolution up to 3840x2160/30Hz
- Support the max baud rate of 3.4G and max bandwidth of 340Mhz
- Support deep color 8/10/12bit
- Support input up to 8 metres AWG26 HDMI standard cable length, output up to 8 metres AWG26 HDMI standard cable length
- Displaying single source, multi-output high-definition signal source from DVD player A/V receiver, set-top box
- 5V/1A power adapter

P-HDMI 1x2-4K



Specifications:

HDMI version	HDMI 1.4b
HDMI resolution	up to 3840x2160/30Hz
Support video format	8/10/12bit Deep color
Support audio format	DTS-HD/Dolby-trueHD/DTS/Dolby-AC3/DSD
Max bandwidth	340MHz
Max baud rate	3.4Gbps
Input cable distance	≤8m AWG26 HDMI standard cable
Output cable distance	≤8m AWG26 HDMI standard cable
HDMI input	1 HDMI
HDMI output	2 HDMI
Max working current	500mA
Specifications of power adapter	input AC (50Hz, 60Hz) 100V-240V; output: DC5V/1A
Operating Temperature range	(-15 °C to +55 °C)
Operating Humidity range	5 to 90%RH (No Condensation)
Dimension (L x W x H)	128x53x23.5 (mm)
Weight	139g

Connection diagram:



Connection and Operation:

1. Connect 1 HDMI cable from HDMI source devices into HDMI Splitter input.
2. Connect 2 HDMI cables from displayers (monitors or projectors) into the HDMI Splitter outputs.
3. Connect 5V power supply to the HDMI 1x2 Splitter.

Package include :

- | | |
|------------------------|------|
| 1. HDMI splitter | 1PCS |
| 2. 5V/1A Power adapter | 1PCS |
| 3. User manual | 1PCS |