

HDMI - HDMI CABLE

CABLES DESIGNED FOR 4K TRANSMISSION

HDMI Type A Male to Type A Male

Cable Construction:

Conductor: 30AWG/28AWG/26AWG Pure Copper
 Insulation: PVC
 Shielded: Aluminum Foil + 30AWG Solid Drain Wire
 Jacket: PVC
 Overall Diameter: 5.5mm/7.3mm/7.3mm

Connectors: 24K Gold Plated HDMI Type A Male to Type A Male
 19 Pin, Male to Male

Version: 1.4, Pass 4K resolution



Cable Marking:

High Speed HDMI™ Cable with Ethernet Exxxxxx **UR**AWM STYLE 20276 80°C 30V VW-1 inhall
 *Or based on customers request.

Applications:

1. Surveillance Cameras
2. TV

Electrical Characteristic:

Voltage: DC300V 5M ohm/10ms
 Insulation Resistance: 10M min
 Contact Resistance: 2 ohm max
 Working Temperature: -25C - +80°C
 Data transfer rate : 10.2Gbps Max
 Differential Impedance: 100±10Ω(TDR)

Test: (100%)

short circuit and open circuit test
 Dislocation test
 Insulation / Jacket test

Packing Length:

1. 1M to 15M
2. 3FT to 50FT

Reference Standards:

1. CE
2. RoHS Compliant

DRAWING:

