

# AY-x6x70 Series Open to Secure (O2S) Readers

## Datasheet



### Introduction

Rosslare's Open to Secure (O2S) family of readers are highly flexible smart card readers that redefine ease of use and high security for RFID access control solutions. The readers support reading from and writing to the secure memory of the world's most accepted RFID technologies – MIFARE Plus and MIFARE Classic EV1.

With MIFARE Plus credentials, you have access to the highest levels of cryptographic security with support for 128-bit AES encrypted communications between reader and credential. With O2S preprogrammed readers and credentials, you can have the highest level of secure access control solutions right out of the box.

The AY-x6x70 and credentials can also come with distinct custom keys and security configuration from the factory.

Choose from a variety of standard configurations to get the functionality that you need – US/UK/Asia or mullion mount, proximity only or proximity & keypad authentication, pigtail or terminal block termination, and multi-format Wiegand or OSDP outputs. You can customize the reader to meet your requirements for maximum configuration flexibility.

### General Description

The AY-x6x70 readers read secure O2S ID data and the CSN from MIFARE Classic EV1 credentials.

### Main Features

- Contactless smart card reader (13.56 MHz)
- Meets ISO14443 Type A Standard
- AES 128-bit encryption during transmission
- Reads O2S ID data from O2S credentials
- Reads CSN of non-O2S credentials
- Output formats:
  - Wiegand (per format on O2S credential)
  - OSDP via RS-485 (selected models)
- RGB multicolor light indicator
- Blue backlit tact switch keypad
- IP68 water and dust resistant for AY-x6270 pigtail models
- IP65 water and dust resistant for AY-x6270 terminal block models and AY-x6370 models
- IK08 vandal resistant for all AY-x6x70 models
- Optical back tamper sensor
- Two LED control and buzzer control inputs
- Pigtail or terminal block connectivity
- Antimicrobial technology reduces level of microbes on reader by up to 99.99%.

## Specifications

ELECTRICAL SPECIFICATIONS		
Operating Voltage Range	6 to 16 VDC	
Input Current at 12V	Standby: 85 mA, Maximum: 110 mA	
OPERATIONAL SPECIFICATIONS		
Read Range (secure credential memory)	AY-H6xx0	AY-G6xx0
MIFARE Classic EV1	40 to 45 mm (1.5 to 1.8 in.)	40 to 45 mm (1.5 to 1.8 in.)
MIFARE Plus	25 mm (1 in.)	30 mm (1.2 in.)
LED Control	Two Inputs: Green LED CTL and RED LED CTL – TTL	
Auxiliary Input	Buzzer CTL or Hold CTL – TTL	
Auxiliary Output	Tamper Output (OC, active low, max. sink current 30 mA)	
Supported Protocol	Wiegand OSDP Secure Channel V2	
Output Format	O2S - Preprogrammed key (per format on O2S credential) Custom - Wiegand 26, 32, 34, 40, 56, 64, 128-bit and customized <sup>1</sup> Keypad: Four user-selectable standard formats available	
Maximum Cable Distance to Controller	Wiegand: 150 m (500 ft) with 18-AWG cable OSDP (RS-485): 1200 m (4,000 ft) with 2x2 18-AWG twisted shielded cable	
Compatible Cards	MIFARE Plus X/S (2K, 4K) and MIFARE EV1 Classic (1K, 4K)	
ENVIRONMENTAL SPECIFICATIONS		
Operating Temperature	-31°C to 63°C (-24°F to 145°F)	
Operating Humidity Range	0% to 95% (non-condensing)	
Outdoor Usage	Weather-resistant, epoxy potted, suitable for outdoor use	
Operating Environment	UV-resistant, epoxy-potted, suitable for indoor and outdoor use <ul style="list-style-type: none"> <li>• IP68 water and dust resistant               <ul style="list-style-type: none"> <li>• AY-G6270 and AY-H6270 pigtail models</li> </ul> </li> <li>• IP65 water and dust resistant               <ul style="list-style-type: none"> <li>• AY-G6270 and AY-H6270 terminal block models</li> <li>• AY-G6370 and AY-H6370</li> </ul> </li> </ul>	
Vandal Resistance	IK08	
Antimicrobial efficacy	Inhibits bacteria proliferation by up to 99.9%	

<sup>1</sup>For custom key operation the AY-x6x70 Series needs to be program using a configuration card.

## MECHANICAL SPECIFICATIONS

Dimensions of Pigtail Models (H x W x D)	AY-G6x70: 145.3 x 42.0 x 23.0 mm (5.7 x 1.7 x 0.9 in.) AY-H6x70: 120.0 x 80.0 x 23.0 mm (4.7 x 3.2 x 0.9 in.)
Dimensions of Terminal Block and OSDP Models (H x W x D)	AY-G6x70: 145.3 x 42.0 x 31.0 mm (5.7 x 1.7 x 1.2 in.) AY-H6x70: 120.0 x 80.0 x 31.0 mm (4.7 x 3.2 x 1.2 in.)
Weight	AY-G6x70: 155 g (5.5 oz) AY-H6x70: 217 g (7.7 oz)

**Interoperability:** The AY-G/H6x70 readers are compatible with Rosslare's controllers and many other third-party Wiegand controllers

**Product Warranty:** 5-year limited product warranty



MIFARE and MIFARE Classic are trademarks of NXP B.V. | MIFARE and MIFARE Plus are registered trademarks of NXP B.V. | Open to Secure® and O2S® are registered trademarks of Rosslare Enterprises Ltd. | All product names, logos, and brands are property of their respective owners.

**DISCLAIMER:** The data contained within Rosslare's materials or documentation is intended to provide only general information about products available for purchase from Rosslare Enterprises Ltd. and its associated companies ("Rosslare"). Reasonable efforts have been made to ensure the accuracy of this information. However, it might contain typographic errors, inaccuracies, or omissions that may relate to product descriptions, visual pictures, specifications, and other details. All technical specifications weights, measures and colors shown, are best approximations. Rosslare can not be held responsible and assumes no legal liability for the accuracy or completeness of the information provided. Rosslare reserves the right to change, delete, or otherwise modify the information, which is represented, at any time, without any prior notice.

© 2022 Rosslare Enterprises Ltd. All rights reserved.

For more information regarding support, visit <https://support.rosslaresecurity.com>.