

Network Keyboard & Control Keyboard & Dome keyboard



Features

- Keyboard to Control
- High Speed Dome (all models)
- Standalone DVR (KBD1000 & NKB1000 only) -
- Network High Speed Dome (NKB1000 only) -
- Network Video Server (NKB1000 only)
- Connection
- NKB1000: RS485, RS422, USB, RS232 & Network
- Three Dimensional Joystick Control of PTZ Functions
- Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Control
- Auxiliary Functions
- On-Screen Menu & User Operation Procedure Tips
- Connect to SmartPSS via USB (NKB1000 only)

NKB1000



Technical Specifications

Model	NKB1000
General	
Keyboard Keypanel	Electromechanical
Joystick	3-axis, vector-solving, with twisting, return to-center head
Keyboard Connector	RJ-45,RS232,RS485,RS422,USB,
Keyboard Communication	Direct Mode, Network Mode
Direct Mode	Interface: RS232/RS485 DVR Protocol: DH2 Dome Protocol: DH-SD/PELCO-D/PELCO-P/PELCO-D1/PELCO-P1.....
Network Mode	Interface: RJ45 DVR/Network Dome: IP Address/Port/Protocol
Display	LCD, 75.2mm x 33.85mm
Environmental	
Power Supply	Power adapter, input 100V~240V 50Hz / 60Hz,output DC12V/1000mA
Power Consumption	5W
Working Temperature	-10°C ~ +55°C
Working Humidity	10%~90%
Atmosphere Pressure	86kpa~106kpa
Dimension	330mmx160(140)mmx37.5(21)mm (W×D×H) (height: 100mm including joystick)
Weight	2.5KG

Winic Technologies USA Inc.

42 Central avenue, Farmingdale, New York 11735

Tel: +631-396-0800

Fax: +631-396-0805

Email:sales@winictech.com

www.winictech.com

*Design and specifications are subject to change without notice.